

*The 7000D series drive-up ATMs offer exceptional value and reliable performance. Plus, they feature scalability and adaptability that make them excellent options for maximum revenue.*

## **Features**

### **Convenient Access**

Rear- or side-access makes it easier to service these ATMs.

### **Reliability**

The Monimax 7000D Series meets demanding performance standards, including UL 291 Level 1 vaults, PCI-certified EPP, ADA compliance, and a fully weatherized exterior.

### **Convenient Options**

- 7000D: drive-up with rear access
- 7000DS: drive-up with side access



***Superior quality, security and value.***

***Only with Nautilus Hyosung.***

*Now offering the most complete line of financial and retail ATMs.*



**The Monimax 7000D Series includes two full-service, drive-up models that include state-of-the-art features at a reasonable price.**

### **Dependable Customer Service**

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

# MONIMAX 7000D

## System Control

- Microsoft® Windows 7® platform
- Intel® Pentium®-IV processor
- Application NDC+, VISA2

## Customer Display

- 10.4" TFT Color LCD
- SVGA (800 x 600) resolution
- Optional sunlight viewable

## Communication

- NDC+ : TCP/IP
- VISA2 : TCP/IP (SSL configurable)  
Dial-up

## Input Type

- 4 x 2 function keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

## Supervisor Operation

- 5.7" Mono display
- 4 x 4 numeric keys
- 4 x 2 function keys

## Card Handling

- Dip-type card reader
- Optional IC card reader,  
EMV Level 1, 2

## Cash Dispensing

- 2,000-note cassette
- Optional cassettes (up to three)

## Depository

### Optional

- Envelope depository

## Printers

- 3.1" graphical thermal receipt printer

## Security

- UL291 Level 1 safe
- Electronic safe lock
- Optional KABA Mas Cencon safe lock

## Miscellaneous

### Optional

- Heater
- Electronic journal (standard)

## Power Supply

- AC 110–230V, 50–60 Hz

## Operating Environment

- Temperature: 32°F–104°F
- With heater: -30°F–110°F
- Humidity: 25%–85%

## Dimension and Weight

- Height: 56.3" (1,430 mm)
- Width: 26.7" (678 mm)
- Depth: 27.5" (700 mm)
- Weight: 1,200 lbs (590 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



 NAUTILUS HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.